

## Cisco ASA 5500 Series Adaptive Security Appliances

Cisco® ASA 5500 Series Adaptive Security Appliances are purpose-built solutions that combine best-in-class security and VPN services with an innovative, extensible services architecture. Designed as a core component of the Cisco Self-Defending Network, the Cisco ASA 5500 Series provides proactive threat defense that stops attacks before they spread through the network, controls network activity and application traffic, and delivers flexible VPN connectivity. The result is a powerful multifunction network security appliance family that provides the security breadth and depth for protecting home office, branch office, small and medium-sized business, enterprise, and data center networks while reducing the overall deployment and operations costs and complexities associated with providing this new level of security.

The Cisco ASA 5500 Series delivers a powerful combination of multiple market-proven technologies in a single platform, making it operationally and economically feasible for organizations to deploy comprehensive security services to more locations. The comprehensive portfolio of services within the Cisco ASA 5500 Series enables customization for location-specific needs through tailored product editions for small to medium-sized businesses and for enterprises. These editions enable superior protection by providing the right services for the right location. Each edition combines a focused set of Cisco ASA 5500 Series services (such as firewall, SSL and IPsec VPN, IPS, and content security services) to meet the needs of specific environments within the enterprise network. By ensuring the security needs of each location are met, the overall network security posture is raised.

**Figure 1.** Cisco ASA 5500 Series Adaptive Security Appliances



The Cisco ASA 5500 Series helps businesses more effectively and efficiently protect their networks while delivering exceptional investment protection through the following key elements:

- **Market-proven security and VPN capabilities**—Full-featured, high-performance firewall, intrusion prevention (IPS), content security, and Secure Sockets Layer/IP Security (SSL/IPsec) VPN technologies deliver robust application security, user- and application-based access control, worm and virus mitigation, malware protection, content filtering, and remote user/site connectivity.
- **Extensible services architecture**—Taking advantage of a modular services processing and policy framework offered by the Cisco ASA 5500 Series, businesses can apply specific security and network services on a per-traffic-flow basis, delivering highly granular policy controls and a wide range of protective services with streamlined traffic processing. The

efficiencies of this policy framework, as well as software and hardware extensibility through user-installable security services modules (SSMs) and security services cards (SSCs), advance the evolution of existing services and the deployment of new services without requiring a platform replacement or performance compromise. With these capabilities, the Cisco ASA 5500 Series provides the foundation for highly customizable security policies and unprecedented services extensibility to help protect against the fast-evolving threat environment.

- **Reduced deployment and operations costs**—The multifunction Cisco ASA 5500 Series allows for platform, configuration, and management standardization, helping to decrease the costs of deployment and ongoing operations.

### Introducing the Cisco ASA 5500 Series

The Cisco ASA 5500 Series includes the Cisco ASA 5505, 5510, 5520, 5540, 5550, and 5580 Adaptive Security Appliances—purpose-built, high-performance security solutions that take advantage of Cisco expertise in developing industry-leading, award-winning security and VPN solutions. The series builds upon proven technologies from Cisco PIX<sup>®</sup> 500 Series Security Appliances, Cisco IPS 4200 Series Sensors, and Cisco VPN 3000 Series Concentrators. Designed as a key component of the Cisco Self-Defending Network, the Cisco ASA 5500 Series provides proactive threat defense that stops attacks before they spread through the network, controls network activity and application traffic, and delivers flexible VPN connectivity. The result is a powerful multifunction network security appliance family that provides the security breadth and depth for protecting small and medium-sized business (SMB), enterprise, and service provider networks while reducing the overall deployment and operations costs and complexities associated with providing this new level of security.

Through its unique Modular Policy Framework (MPF), the Cisco ASA 5500 Series brings a new level of security and policy control to applications and networks. MPF allows businesses to adapt and extend the profile of the Cisco ASA 5500 Series through highly customizable, flow-specific security policies tailored to application requirements while providing performance and extensibility through user-installable SSMs. This adaptable architecture enables businesses to rapidly deploy security services when and where they are needed, such as tailoring inspection techniques to specific application and user needs or adding additional intrusion prevention and content security such as those delivered by the Adaptive Inspection and Prevention (AIP) and Content Security and Control (CSC) SSM. Furthermore, the modular hardware architecture of the Cisco ASA 5500 Series along with flexible MPF enables the integration of future network and security, extending the outstanding investment protection provided by the Cisco ASA 5500 Series, and allowing businesses to adapt their network defenses to new threats as they arise.

All Cisco ASA 5500 Series appliances include maximum IPsec VPN users on the base system; SSL VPN is licensed and purchased separately. By converging SSL and IPsec VPN services with comprehensive threat defense technologies, the Cisco ASA 5500 Series provides highly customizable network access tailored to meet the requirements of diverse deployment environments while providing advanced endpoint and network-level security.

### Cisco ASA 5505 Adaptive Security Appliance

The Cisco ASA 5505 Adaptive Security Appliance is a next-generation, full-featured security appliance for small business, branch office, and enterprise teleworker environments. The Cisco ASA 5505 delivers high-performance firewall, SSL and IPsec VPN, and rich networking services in

a modular, “plug-and-play” appliance. Using the integrated Cisco Adaptive Security Device Manager, the Cisco ASA 5505 can be rapidly deployed and easily managed, enabling businesses to minimize operations costs. The Cisco ASA 5505 features a flexible 8-port 10/100 Fast Ethernet switch, whose ports can be dynamically grouped to create up to three separate VLANs for home, business, and Internet traffic for improved network segmentation and security. The Cisco ASA 5505 provides two Power over Ethernet (PoE) ports, enabling simplified deployment of Cisco IP phones with zero-touch secure voice over IP (VoIP) capabilities, and deployment of external wireless access points for extended network mobility. The Cisco ASA 5505 also provides significant expandability and investment protection through its modular design, similar to the rest of the Cisco ASA 5500 Series, offering both an external expansion slot and multiple USB ports that enable the addition of services in the future.

As business needs grow, customers can install a Security Plus upgrade license, enabling the Cisco ASA 5505 Adaptive Security Appliance to scale to support a higher connection capacity and a higher number of IPsec VPN users, add full DMZ support, and integrate into switched network environments through VLAN trunking support. Furthermore, this upgrade license maximizes business continuity by enabling support for redundant ISP connections and stateless Active/Standby high-availability services. This combination of market-leading security and VPN services, advanced networking features, flexible remote management capabilities, and future extensibility makes the Cisco ASA 5505 an excellent choice for businesses requiring a best-in-class small business, branch office, or enterprise teleworker security solution.

Table 1 lists features of the Cisco ASA 5505.

**Table 1.** Cisco ASA 5505 Adaptive Security Appliance Platform Capabilities and Capacities

Feature	Description
<b>Firewall Throughput</b>	Up to 150 Mbps
<b>VPN Throughput</b>	Up to 100 Mbps
<b>Concurrent Sessions</b>	10,000/25,000**
<b>IPsec VPN Peers</b>	10; 25**
<b>SSL VPN Peer License Levels*</b>	10 or 25
<b>Interfaces</b>	8-port Fast Ethernet switch with dynamic port grouping (including 2 PoE ports)
<b>Virtual Interfaces (VLANs)</b>	3 (no trunking support) / 20 (with trunking support)**
<b>High Availability</b>	Not supported; stateless Active/Standby and redundant ISP support**

\* Separately licensed feature; includes two with the base system

\*\* Upgrade available with Cisco ASA 5505 Security Plus license

## Cisco ASA 5510 Adaptive Security Appliance

The Cisco ASA 5510 Adaptive Security Appliance delivers advanced security and networking services for small and medium-sized businesses and enterprise remote/branch offices in an easy-to-deploy, cost-effective appliance. These services can be easily managed and monitored by the integrated, Cisco Adaptive Security Device Manager application, thus reducing the overall deployment and operations costs associated with providing this high level of security. The Cisco ASA 5510 Adaptive Security Appliance provides high-performance firewall and VPN services and five integrated 10/100 Fast Ethernet interfaces. It optionally provides high-performance intrusion prevention and worm mitigation services through the AIP

SSM, or comprehensive malware protection services through the CSC SSM. This unique combination of services on a single platform makes the Cisco ASA 5510 an excellent choice for businesses requiring a cost-effective, extensible, DMZ-enabled security solution.

As business needs grow, customers can install a Security Plus license, upgrading two of the Cisco ASA 5510 Adaptive Security Appliance interfaces to Gigabit Ethernet and enabling integration into switched network environments through VLAN support. This upgrade license maximizes business continuity by enabling Active/Active and Active/Standby high-availability services. Using the optional security context capabilities of the Cisco ASA 5510 Adaptive Security Appliance, businesses can deploy up to five virtual firewalls within an appliance to enable compartmentalized control of security policies on a departmental level. This virtualization strengthens security and reduces overall management and support costs while consolidating multiple security devices into a single appliance.

Businesses can extend their SSL and IPsec VPN capacity to support a larger number of mobile workers, remote sites, and business partners. Businesses can scale up to 250 SSL VPN peers on each Cisco ASA 5510 by installing an SSL VPN upgrade license; 250 IPsec VPN peers are supported on the base platform. VPN capacity and resiliency can also be increased by taking advantage of the Cisco ASA 5510's integrated VPN clustering and load-balancing capabilities (available if a Security Plus license is installed). The Cisco ASA 5510 supports up to 10 appliances in a cluster, supporting a maximum of 2500 SSL VPN peers or 2500 IPsec VPN peers per cluster.

Table 2 lists features of the Cisco ASA 5510.

**Table 2.** Cisco ASA 5510 Adaptive Security Appliance Platform Capabilities and Capacities

Feature	Description
Firewall Throughput	Up to 300 Mbps
Concurrent Threat Mitigation Throughput (firewall + IPS services)	<ul style="list-style-type: none"> <li>Up to 150 Mbps with AIP SSM-10</li> <li>Up to 300 Mbps with AIP SSM-20</li> </ul>
VPN Throughput	Up to 170 Mbps
Concurrent Sessions	50,000; 130,000***
IPsec VPN Peers	250
SSL VPN Peer License Levels*	10, 25, 50, 100, or 250
Security Contexts	Up to 5**
Interfaces***	Five Fast Ethernet ports; 2 Gigabit Ethernet + 3 Fast Ethernet***
Virtual Interfaces (VLANs)	50; 100***
Scalability***	VPN clustering and load balancing
High Availability	Not supported; Active/Active, Active/Standby***

\* Separately licensed feature; includes two with the base system

\*\* Separately licensed feature; includes two with the Cisco ASA 5510 Security Plus license

\*\*\* Upgrade available with Cisco ASA 5510 Security Plus license

### Cisco ASA 5520 Adaptive Security Appliance

The Cisco ASA 5520 Adaptive Security Appliance delivers security services with Active/Active high availability and Gigabit Ethernet connectivity for medium-sized enterprise networks in a modular, high-performance appliance. With four Gigabit Ethernet interfaces and support for up to 100 VLANs, businesses can easily deploy the Cisco ASA 5520 into multiple zones within their network. The Cisco ASA 5520 Adaptive Security Appliance scales with businesses as their network security requirements grow, delivering solid investment protection.

Businesses can extend their SSL and IPsec VPN capacity to support a larger number of mobile workers, remote sites, and business partners. Businesses can scale up to 750 SSL VPN peers on each Cisco ASA 5520 by installing an SSL VPN upgrade license; 750 IPsec VPN peers are supported on the base platform. VPN capacity and resiliency can also be increased by taking advantage of the Cisco ASA 5520's integrated VPN clustering and load-balancing capabilities. The Cisco ASA 5520 supports up to 10 appliances in a cluster, supporting a maximum of 7500 SSL VPN peers or 7500 IPsec VPN peers per cluster. The advanced application-layer security and content security defenses provided by the Cisco ASA 5520 can be extended by deploying the high-performance intrusion prevention and worm mitigation capabilities of the AIP SSM, or the comprehensive malware protection of the CSC SSM. Using the optional security context capabilities of the Cisco ASA 5520 Adaptive Security Appliance, businesses can deploy up to 20 virtual firewalls within an appliance to enable compartmentalized control of security policies on a departmental level. This virtualization strengthens security and reduces overall management and support costs while consolidating multiple security devices into a single appliance.

Table 3 lists features of the Cisco ASA 5520.

**Table 3.** Cisco ASA 5520 Adaptive Security Appliance Platform Capabilities and Capacities

Feature	Description
Firewall Throughput	Up to 450 Mbps
Concurrent Threat Mitigation Throughput (firewall + IPS services)	<ul style="list-style-type: none"> <li>Up to 225 Mbps with AIP SSM-10</li> <li>Up to 375 Mbps with AIP SSM-20</li> </ul>
VPN Throughput	Up to 225 Mbps
Concurrent Sessions	280,000
IPsec VPN Peers	750
SSL VPN Peer License Levels*	10, 25, 50, 100, 250, 500, or 750
Security Contexts*	Up to 20
Interfaces	4 Gigabit Ethernet ports and 1 Fast Ethernet port
Virtual Interfaces (VLANs)	150
Scalability	VPN clustering and load balancing
High Availability	Active/Active, Active/Standby

\* Separately licensed feature; includes two with base system

### Cisco ASA 5540 Adaptive Security Appliance

The Cisco ASA 5540 Adaptive Security Appliance delivers high-performance, high-density security services with Active/Active high availability and Gigabit Ethernet connectivity for medium-sized and large enterprise and service-provider networks, in a reliable, modular appliance. With four Gigabit Ethernet interfaces and support for up to 100 VLANs, businesses can use the Cisco ASA 5540 to segment their network into numerous zones for improved security. The Cisco ASA 5540 Adaptive Security Appliance scales with businesses as their network security requirements grow, delivering exceptional investment protection and services scalability. The advanced network and application-layer security services and content security defenses provided by the Cisco ASA 5540 Adaptive Security Appliance can be extended by deploying the AIP SSM for high-performance intrusion prevention and worm mitigation.

Businesses can scale their SSL and IPsec VPN capacity to support a larger number of mobile workers, remote sites, and business partners. Businesses can scale up to 2500 SSL VPN peers on each Cisco ASA 5540 by installing an SSL VPN upgrade license; 5000 IPsec VPN peers are

supported on the base platform. VPN capacity and resiliency can also be increased by taking advantage of the Cisco ASA 5540's integrated VPN clustering and load-balancing capabilities. The Cisco ASA 5540 supports up to 10 appliances in a cluster, supporting a maximum of 25,000 SSL VPN peers or 50,000 IPsec VPN peers per cluster. Using the optional security context capabilities of the Cisco ASA 5540 Adaptive Security Appliance, businesses can deploy up to 50 virtual firewalls within an appliance to enable compartmentalized control of security policies on a per-department or per-customer basis, and deliver reduced overall management and support costs.

Table 4 lists features of the Cisco ASA 5540.

**Table 4.** Cisco ASA 5540 Adaptive Security Appliance Platform Capabilities and Capacities

Feature	Description
Firewall Throughput	Up to 650 Mbps
Concurrent Threat Mitigation Throughput (firewall + IPS services)	Up to 450 Mbps with AIP SSM-20
VPN Throughput	Up to 325 Mbps
Concurrent Sessions	400,000
IPsec VPN Peers	5000
SSL VPN Peer License Levels*	10, 25, 50, 100, 250, 500, 750, 1000, and 2500
Security Contexts*	Up to 50*
Interfaces	4 Gigabit Ethernet ports and 1 Fast Ethernet port
Virtual Interfaces (VLANs)	200
Scalability	VPN clustering and load balancing
High Availability	Active/Active, Active/Standby

\* Separately licensed feature; includes two with base system

### Cisco ASA 5550 Adaptive Security Appliance

The Cisco ASA 5550 Adaptive Security Appliance delivers gigabit-class security services with Active/Active high availability and fiber and Gigabit Ethernet connectivity for large enterprise and service-provider networks in a reliable, 1-rack-unit form factor. Using its eight Gigabit Ethernet interfaces, four Small Form-Factor Pluggable (SFP) fiber interfaces\*, and support for up to 200 VLANs, businesses can segment their network into numerous high-performance zones for improved security.

The Cisco ASA 5550 Adaptive Security Appliance scales with businesses as their network security requirements grow, delivering exceptional investment protection and services scalability.

Businesses can scale their SSL and IPsec VPN capacity to support a larger number of mobile workers, remote sites, and business partners. Businesses can scale up to 5000 SSL VPN peers on each Cisco ASA 5550 by installing an SSL VPN upgrade license; 5000 IPsec VPN peers are supported on the base platform. VPN capacity and resiliency can also be increased by taking advantage of the Cisco ASA 5550's integrated VPN clustering and load-balancing capabilities. The Cisco ASA 5550 supports up to 10 appliances in a cluster, supporting a maximum of 50,000 SSL VPN peers or 50,000 IPsec VPN peers per cluster. Using the optional security context capabilities of the Cisco ASA 5550 Adaptive Security Appliance, businesses can deploy up to 50 virtual firewalls within an appliance to enable compartmentalized control of security policies on a per-department or per-customer basis, and deliver reduced overall management and support costs.

**Note:** The system provides a total of 12 Gigabit Ethernet ports, of which only 8 can be in service at any time. Businesses can choose between copper or fiber connectivity, providing flexibility for data center, campus, or enterprise edge connectivity.

Table 5 lists features of the Cisco ASA 5550.

**Table 5.** Cisco ASA 5550 Adaptive Security Appliance Platform Capabilities and Capacities

Feature	Description
Firewall Throughput	Up to 1.2 Gbps
VPN Throughput	Up to 425 Mbps
Concurrent Sessions	650,000
IPsec VPN Peers	5000
SSL VPN Peer License Levels*	10, 25, 50, 100, 250, 500, 750, 1000, 2500, and 5000
Security Contexts*	Up to 50
Interfaces	8 Gigabit Ethernet ports, 4 SFP fiber ports, and 1 Fast Ethernet port
Virtual Interfaces (VLANs)	250
Scalability	VPN clustering and load balancing
High Availability	Active/Active, Active/Standby

\* Separately licensed feature; includes two with base system

### Cisco ASA 5580 Adaptive Security Appliances

The Cisco ASA 5580-20 and 5580-40 Adaptive Security Appliances deliver multigigabit security services for large enterprise, data center, and service-provider networks in a robust, 4-rack-unit form factor. The Cisco ASA 5580 accommodates high-density copper and optical interfaces with scalability from Fast Ethernet to 10Gigabit Ethernet, enabling unparalleled security and deployment flexibility. Cisco ASA 5580 Adaptive Security Appliances include six interface card expansion slots with support for up to 24 Gigabit Ethernet interfaces or up to 12 10Gigabit Ethernet interfaces that simplify provisioning and enable campus segmentation. Furthermore, this high-density design enables security virtualization while retaining physical segmentation desired in managed security and infrastructure consolidation applications.

The Cisco ASA 5580 Series are offered at two performance levels: the Cisco ASA 5580-20 with 6.5 Gbps firewall performance, and the high-end Cisco ASA 5580-40 with 14 Gbps firewall performance. Their multicore, multiprocessor architecture delivers radical scalability for the most demanding network security and VPN concentration applications. Real-time applications can be transparently secured thanks to the extremely low latency, high session concurrency, and connection setup rates. Cisco ASA 5580 Adaptive Security Appliances can also be clustered to provide improved reliability and scalability, with support for up to 100,000 SSL or IPsec remote-access clients when deploying 10 appliances in a cluster. Additional features including security virtualization through the use of security contexts and VLANs, increase service velocity while reducing operational and administrative overhead.

Table 6 lists features of the Cisco ASA 5580 Security Appliances.

**Table 6.** Cisco ASA 5580 Adaptive Security Appliance Platform Capabilities and Capacities

Feature	ASA 5580-20	ASA 5580-40
Max Firewall Throughput	5 Gbps (real-world HTTP), 10 Gbps (jumbo frames)	10 Gbps (real-world HTTP), 20 Gbps (jumbo frames)

Feature	ASA 5580-20	ASA 5580-40
<b>Max VPN Throughput</b>	1 Gbps	1 Gbps
<b>Concurrent Sessions</b>	1,000,000	2,000,000
<b>IPsec VPN Peers</b>	10000	10000
<b>SSL VPN Peer License Levels*</b>	10, 25, 50, 100, 250, 500, 750, 1000, 2500, 5000, and 10,000	10, 25, 50, 100, 250, 500, 750, 1000, 2500, 5000, and 10000
<b>Security Contexts</b>	Up to 50*	Up to 50*
<b>Interfaces</b>	2 Gigabit Ethernet management	2 Gigabit Ethernet management
<b>Interface Card Slots</b>	6	6
<b>Interface Card Options</b>	<ul style="list-style-type: none"> <li>• 4 Port 10/100/1000, RJ45</li> <li>• 4 Port Gigabit Ethernet fiber, SR, LC</li> <li>• 2 Port 10Gigabit Ethernet fiber, SR, LC</li> </ul>	<ul style="list-style-type: none"> <li>• 4 Port 10/100/1000, RJ45</li> <li>• 4 Port Gigabit Ethernet fiber, SR, LC</li> <li>• 2 Port 10Gigabit Ethernet fiber, SR, LC</li> </ul>
<b>Virtual interfaces (VLANs)</b>	100 (250**)	100 (250**)
<b>Scalability</b>	VPN clustering and load balancing	VPN clustering and load balancing
<b>High Availability</b>	Active/Active, Active/Standby	Active/Active, Active/Standby
<b>Redundant Power</b>	Supported, second power supply optional	Supported, second power supply optional






\* Separately licensed feature; includes two with base system

\*\* Supported in a future software release

## Specifications

Table 7, 8 provides a comparison of the Cisco ASA 5505, 5510, 5520, 5540, 5550, and 5580 Adaptive Security Appliances.

**Table 7.** Characteristics of Cisco ASA 5500 Series Adaptive Security Appliances

	Cisco ASA 5505	Cisco ASA 5510	Cisco ASA 5520	Cisco ASA 5540	Cisco ASA 5550
					
<b>Users/Nodes</b>	10, 50, or unlimited	Unlimited	Unlimited	Unlimited	Unlimited
<b>Firewall Throughput</b>	Up to 150 Mbps	Up to 300 Mbps	Up to 450 Mbps	Up to 650 Mbps	Up to 1.2 Gbps
<b>Concurrent Threat Mitigation Throughput (firewall + IPS services)</b>	Not available	<ul style="list-style-type: none"> <li>• Up to 150 Mbps with AIP-SSM-10</li> <li>• Up to 300 Mbps with AIP-SSM-20</li> </ul>	<ul style="list-style-type: none"> <li>• Up to 225 Mbps with AIP-SSM-10</li> <li>• Up to 375 Mbps with AIP-SSM-20</li> </ul>	Up to 450 Mbps with AIP-SSM-20	Not available
<b>3DES/AES VPN Throughput</b>	Up to 100 Mbps	Up to 170 Mbps	Up to 225 Mbps	Up to 325 Mbps	Up to 425 Mbps
<b>IPsec VPN Peers</b>	10; 25*	250	750	5000	5000
<b>SSL VPN Peers* included/maximum)</b>	2/25	2/250	2/750	2/2500	2/5000
<b>Concurrent Connections</b>	10,000; 25,000*	50,000; 130,000*	280,000	400,000	650,000
<b>New Connections/Second</b>	4000	9000	12,000	25,000	36,000



	Cisco ASA 5505	Cisco ASA 5510	Cisco ASA 5520	Cisco ASA 5540	Cisco ASA 5550
<b>Integrated Network Ports</b>	8-port Fast Ethernet switch (including 2 PoE ports)	5 Fast Ethernet ports; 2 Gigabit Ethernet + 3 Fast Ethernet ports*	4 Gigabit Ethernet, 1 Fast Ethernet	4 Gigabit Ethernet, 1 Fast Ethernet	8 Gigabit Ethernet, 4 SFP Fiber, 1 Fast Ethernet
<b>Virtual Interfaces (VLANs)</b>	3 (no trunking support)/20 (with trunking support)*	50 /100*	150	200	250
<b>Security Contexts (included/maximum)*</b>	0/0	0/0 (Base); 2/5 (Security Plus)	2/20	2/50	2/50
<b>High Availability</b>	Not supported; stateless Active/Standby and redundant ISP support*	Not supported; Active/Active and Active/Standby**	Active/Active and Active/Standby	Active/Active and Active/Standby	Active/Active and Active/Standby
<b>Expansion Slot</b>	1, SSC	1, SSM	1, SSM	1, SSM	0
<b>User-Accessible Flash slot</b>	0	1	1	1	1
<b>USB 2.0 Ports</b>	3 (1 on front, 2 on rear)	2	2	2	2
<b>Serial Ports</b>	1 RJ-45 console	2 RJ-45, console and auxiliary	2 RJ-45, console and auxiliary	2 RJ-45, console and auxiliary	2 RJ-45, console and auxiliary
<b>Rack-Mountable</b>	Yes, with rack-mount kit (available in the future)	Yes	Yes	Yes	Yes
<b>Wall-Mountable</b>	Yes, with wall-mount kit (available in the future)	Not Available	Not Available	Not Available	Not Available
<b>Security Lock Slot (for Physical Security)</b>	Yes	Not Available	Not Available	Not Available	Not Available
<b>Technical Specifications</b>					
Memory	256 MB	256 MB	512 MB	1 GB	4 GB
Minimum system flash	64 MB	64 MB	64 MB	64 MB	64 MB
System bus	Multibus architecture	Multibus architecture	Multibus architecture	Multibus architecture	Multibus architecture
<b>Environmental Operating Ranges</b>					
<b>Operating</b>					
Temperature	32 to 104°F (0 to 40°C)	32 to 104°F (0 to 40°C)			
Relative humidity	5 to 95 percent noncondensing	5 to 95 percent noncondensing			
Altitude	Designed and tested for: 0 to 9840 ft (3000 m). Agency approved for: 2000 m				
Shock	1.14 m/sec (45 in./sec) ½ sine input	1.14 m/sec (45 in./sec) 1/2 sine input			
Vibration	0.41 Grms2 (3 to 500 Hz) random input	0.41 Grms2 (3 to 500 Hz) random input			
Acoustic noise	0 dBa max	60 dBa max			
<b>Nonoperating</b>					

	Cisco ASA 5505	Cisco ASA 5510	Cisco ASA 5520	Cisco ASA 5540	Cisco ASA 5550
Temperature	-13 to 158°F (-25 to 70°C)	-13 to 158°F (-25 to 70°C)			
Relative humidity	5 to 95 percent noncondensing	5 to 95 percent noncondensing			
Altitude	0 to 15,000 ft (4570 m)	0 to 15,000 ft (4570 m)			
Shock	30 G	30 G			
Vibration	0.41 Grms2 (3 to 500 Hz) random input	0.41 Grms2 (3 to 500 Hz) random input			
<b>Power</b>					
<b>Input (per power supply)</b>					
Range line voltage	100 to 240 VAC	100 to 240 VAC			
Normal line voltage	100 to 240 VAC	100 to 240 VAC			
Current	1.8A	3A			
Frequency	50/60 Hz	47/63 Hz, single-phase			
<b>Output</b>					
Steady state	20W	150W			
Maximum peak	96W	190W			
Maximum heat dissipation	72 BTU/hr	648 BTU/hr			
<b>Physical Specifications</b>					
Form factor	Desktop	1 RU, 19-in. rack-mountable			
Dimensions (H x W x D)	1.75 x 7.89 x 6.87 in. (4.45 x 20.04 x 17.45 cm)	1.75 x 17.5 x 14.25 in. (4.45 x 20.04 x 36.20 cm)			
Weight (with power supply)	4.0 lb (1.8 kg)	20.0 lb (9.07 kg)	22.0 lb (10 kg)		
<b>Regulatory and Standards Compliance</b>					
Safety	UL 60950, CSA C22.2 No. 60950, EN 60950 IEC 60950, AS/NZS60950				
Electromagnetic compatibility (EMC)	CE marking, FCC Part 15 Class B, AS/NZS CISPR22 Class B, VCCI Class B, EN55022 Class B, CISPR22 Class B, EN61000-3-2, EN61000-3-3	CE marking, FCC Part 15 Class A, AS/NZS CISPR22 Class A, VCCI Class A, EN55022 Class A, CISPR22 Class A, EN61000-3-2, EN61000-3-3			
Industry certifications	In process: Common Criteria EAL4, FIPS 140-2 Level 2	Common Criteria EAL4+ US DoD Application-Level Firewall for Medium-Robustness Environments, FIPS 140-2 Level 2, NEBS Level 3. Common Criteria EAL2 for IPS on AIP SSM.			In process: Common Criteria EAL4, FIPS 140-2 Level 2

\* Available through an upgrade license

**Table 8.** Characteristics of Cisco ASA 5580 Series Adaptive Security Appliances

	Cisco ASA 5580-20	Cisco ASA 5580-40
		

	Cisco ASA 5580-20	Cisco ASA 5580-40
Users/Nodes	Unlimited	Unlimited
Firewall Throughput	Up to 5 Gbps (real-world HTTP), 10 Gbps (jumbo frames)	Up to 10 Gbps (real-world HTTP), 20 Gbps (jumbo frames)
3DES/AES VPN Throughput	1 Gbps	1 Gbps
IPsec VPN Peers	10,000	10,000
SSL VPN Peers*	2/10,000	2/10,000
Concurrent Connections	1,000,000	2,000,000
New Connections/Second	90,000	150,000
Packets/Second (64 byte)	2,500,000	4,000,000
Integrated Network Ports	2 Gigabit Ethernet management	2 Gigabit Ethernet management
Interface Card Slots	6	6
Interface Card Options	<ul style="list-style-type: none"> <li>• 4 Port 10/100/1000, RJ45</li> <li>• 4 Port Gigabit Ethernet fiber, SR, LC</li> <li>• 2 Port 10Gigabit Ethernet fiber, SR, LC</li> </ul>	<ul style="list-style-type: none"> <li>• 4 Port 10/100/1000, RJ45</li> <li>• 4 Port Gigabit Ethernet fiber, SR, LC</li> <li>• 2 Port 10Gigabit Ethernet fiber, SR, LC</li> </ul>
Virtual Interfaces	100 (250**)	100 (250**)
Security Contexts*	2/50	2/50
High Availability	Active/Active and Active/Standby	Active/Active and Active/Standby
Redundant Power	Supported, second power supply optional	Supported, second power supply optional
Interface Expansion	6 interface expansion card slots	6 interface expansion card slots
USB 2.0 Ports	2	2
Serial Ports	1 RJ-45, console	1 RJ-45, console
Rack-Mountable	Yes, rails included	Yes, rails included
<b>Technical Specifications</b>		
Memory	8 GB	12 GB
Minimum system flash	1 GB	1 GB
System bus	Multibus architecture	Multibus architecture
<b>Environmental Operating Ranges</b>		
Operating temperature	50 to 95°F (10 to 35°C)	
Relative humidity	10 to 90 percent noncondensing	
Altitude	Designed and tested for: 0 to 10,000 ft (3050 m). Agency Approved for: 2000 m	
Noise	55 dBa max	
<b>Nonoperating</b>		
Temperature	-22 to 140°F (-30 to 60°C)	
Relative humidity	5 to 95 percent noncondensing	
Altitude	0 to 30,000 ft (9144 m)	
<b>Power</b>		
<b>Input (per power supply)</b>		
Range line voltage	100 to 240 VAC	
Normal line voltage	100 to 240 VAC	
Current	12A	
Frequency	50/60 Hz	
<b>Output</b>		
Steady state	800W	
Maximum peak	800W	
Maximum heat dissipation	4070 BTU/hr	

	Cisco ASA 5580-20	Cisco ASA 5580-40
<b>Physical Specifications</b>		
Form factor	4 RU, 19-in. rack-mountable	
Dimensions (H x W x D)	6.94 x 19 x 26.5 in. (17.6 x 48.3 x 67.3 cm)	
Weight (with single power supply)	66 lb (29.9 kg)	
<b>Regulatory and Standards</b>		
Safety	UL 60950, CSA C22.2 No. 60950, EN 60950 IEC 60950, AS/NZS60950	
Electromagnetic compatibility (EMC)	CE marking, FCC Part 15 Class A, AS/NZS CISPR22 Class A, VCCI Class A, EN55022 Class A, CISPR22 Class A, EN61000-3-2, EN61000-3-3	

\* Available through an upgrade license

\*\* Supported in a future ASA software release.

## Security Services Modules

The Cisco ASA 5500 Series brings a new level of integrated security performance to networks with its unique AIM services and multiprocessor hardware architecture. This architecture allows businesses to adapt and extend the high-performance security services profile of the Cisco ASA 5500 Series. Customers can add additional high-performance services using security services modules with dedicated security co-processors, and can custom-tailor flow-specific policies using a highly flexible policy framework. This adaptable architecture enables businesses to deploy new security services when and where they are needed, such as adding the broad range of intrusion prevention and advanced anti-worm services delivered by the AIP SSM or the comprehensive malware protection and content security services enabled by the CSC SSM. Further, the architecture allows Cisco to introduce new services to address new threats, delivering businesses outstanding investment protection for the Cisco ASA 5500 Series.

### Cisco ASA 5500 Series Advanced Inspection and Prevention Module

The Cisco ASA 5500 Series AIP SSM is an inline, network-based solution that accurately identifies, classifies, and stops malicious traffic before it affects business continuity. It combines inline prevention services with innovative technologies, resulting in total confidence in the provided protection of the deployed IPS solution, without the fear of legitimate traffic being dropped. The AIP SSM also offers comprehensive network protection through its unique ability to collaborate with other network security resources, providing a proactive approach to protecting the network. It uses accurate inline prevention technologies that provide unparalleled confidence to take preventive action on a broader range of threats without the risk of dropping legitimate traffic. These unique technologies offer intelligent, automated, contextual analysis of data and help ensure that businesses are getting the most out of their intrusion prevention solutions. Furthermore, the AIP SSM uses multivector threat identification to protect the network from policy violations, vulnerability exploitations, and anomalous activity through detailed inspection of traffic in Layers 2 through 7.

Table 9 details the two AIP SSM models that are available, and their respective performance and physical characteristics.

**Table 9.** Characteristics of Cisco ASA 5500 Series AIP SSMs



	Cisco ASA 5500 Series SSM AIP-10	Cisco ASA 5500 Series SSM AIP-20
		

	Cisco ASA 5500 Series SSM AIP-10	Cisco ASA 5500 Series SSM AIP-20
Concurrent threat mitigation throughput (firewall + IPS services)	<ul style="list-style-type: none"> <li>• 150 Mbps with Cisco ASA 5510</li> <li>• 225 Mbps with Cisco ASA 5520</li> </ul>	<ul style="list-style-type: none"> <li>• 300 Mbps with Cisco ASA 5510</li> <li>• 375 Mbps with Cisco ASA 5520</li> <li>• 450 Mbps with Cisco ASA 5540</li> </ul>
<b>Technical Specifications</b>		
Memory	1 GB	2 GB
Flash	256 MB	256 MB
<b>Environmental Operating Ranges</b>		
<b>Operating</b>		
Temperature	32 to 104°F (0 to 40°C)	
Relative humidity	5 to 95 percent noncondensing	
<b>Nonoperating</b>		
Temperature	−13 to 158°F (−25 to 70°C)	
Power consumption	90W maximum	
<b>Physical Specifications</b>		
Dimensions (H x W x D)	1.70 x 6.80 x 12.25 in. (4.32 x 17.27 x 31.12 cm)	
Weight (with power supply)	3.00 lb (1.36 kg)	
<b>Regulatory and Standards Compliance</b>		
Safety	UL 60950, CSA C22.2 No. 60950, EN 60950 IEC 60950, AS/NZS60950	
Electromagnetic compatibility (EMC)	CE marking, FCC Part 15 Class A, AS/NZS CISPR22 Class A, VCCI Class A, EN55022 Class A, CISPR22 Class A, EN61000-3-2, EN61000-3-3	

### Cisco ASA 5500 Series Content Security and Control Module

The Cisco ASA 5500 Series CSC SSM delivers industry-leading threat protection and content control at the Internet edge, providing comprehensive antivirus, anti-spyware, file blocking, anti-spam, anti-phishing, URL blocking and filtering, and content filtering—in an easy-to-manage solution. The CSC SSM bolsters the Cisco ASA 5500 Series' strong security capabilities, providing customers with additional protection and control over the content of their business communications. The module provides additional flexibility and choice over the functioning and deployment of Cisco ASA 5500 Series appliances. Licensing options enable organizations to customize the features and capabilities to each group's needs, with features that include advanced content services and increased user capacity. The CSC SSM ships with a default feature set that provides antivirus, anti-spyware, and file blocking services. A Plus license is available for each CSC SSM at an additional charge, delivering capabilities such as anti-spam, anti-phishing, URL blocking and filtering, and content control services. Businesses can extend the user capacity of the CSC SSM by purchasing and installing additional user licenses. A detailed listing of these options is shown in Table 10 and in the CSC SSM data sheet.

**Table 10.** Characteristics of Cisco ASA 5500 Series CSC SSMs

	Cisco ASA 5500 Series CSC-SSM-10	Cisco ASA 5500 Series CSC-SSM-20
		
Supported Platforms	<ul style="list-style-type: none"> <li>• Cisco ASA 5510</li> <li>• Cisco ASA 5520</li> </ul>	<ul style="list-style-type: none"> <li>• Cisco ASA 5510</li> <li>• Cisco ASA 5520</li> <li>• Cisco ASA 5540</li> </ul>
<b>Standard and Optional Features</b>		
Standard user license	50 users	500 users


	Cisco ASA 5500 Series CSC-SSM-10	Cisco ASA 5500 Series CSC-SSM-20
Standard feature set	Antivirus, anti-spyware, file blocking	
Optional user upgrades (total users)	<ul style="list-style-type: none"> <li>• 100 users</li> <li>• 250 users</li> <li>• 500 users</li> </ul>	<ul style="list-style-type: none"> <li>• 750 users</li> <li>• 1000 users</li> </ul>
Optional feature upgrades	Plus License—Adds anti-spam, anti-phishing, URL blocking and filtering, and content control	
<b>Technical Specifications</b>		
Memory	1 GB	2 GB
System flash	256 MB	256 MB
<b>Environmental Operating Ranges</b>		
<b>Operating</b>		
Temperature	32 to 104°F (0 to 40°C)	
Relative humidity	10 to 90 percent, noncondensing	
<b>Nonoperating</b>		
Temperature	–13 to 158°F (–25 to 70°C)	
Power consumption	90W maximum	
<b>Physical Specifications</b>		
Dimensions (H x W x D)	1.70 x 6.80 x 12.25 in. (4.32 x 17.27 x 31.12 cm)	
Weight (with power supply)	3.00 lb (1.36 kg)	
<b>Regulatory and Standards Compliance</b>		
Safety	UL 60950, CSA C22.2 No. 60950, EN 60950 IEC 60950, AS/NZS60950	
Electromagnetic compatibility (EMC)	CE marking, FCC Part 15 Class A, AS/NZS CISPR22 Class A, VCCI Class A, EN55022 Class A, CISPR22 Class A, EN61000-3-2, EN61000-3-3	

### Cisco ASA 5500 Series 4-Port Gigabit Ethernet Module

The Cisco ASA 4-Port Gigabit Ethernet SSM enables businesses to better segment network traffic into separate security zones, providing more granular security for their network environment.

These zones can range from the Internet to internal corporate departments/sites to DMZs. This high-performance module supports both copper and optical connection options by including four 10/100/1000 copper RJ-45 ports and four SFP ports. Businesses can choose between copper or fiber connectivity for each of the four ports, providing flexibility for data center, campus, or enterprise edge connectivity (with a maximum of four ports in service concurrently). The module extends the I/O profile of the Cisco ASA 5500 Series to a total of five Fast Ethernet and four Gigabit Ethernet ports on the Cisco ASA 5510, and eight Gigabit Ethernet ports and one Fast Ethernet port on Cisco ASA 5520 and 5540 appliances (Table 11).

**Table 11.** Characteristics of Cisco ASA 5500 Series 4-Port Gigabit Ethernet SSM




	Cisco ASA 5500 Series 4-Port GE SSM
	
<b>Technical Specifications</b>	
Integrated LAN ports	Four 10/100/1000BASE-T (RJ)
Integrated SFP ports	Four (Gigabit Ethernet Optical SFP 1000BASE-SX or LX/LH transceiver supported)

Cisco ASA 5500 Series 4-Port GE SSM	
<b>Environmental Operating Ranges</b>	
<b>Operating</b>	
Temperature	32 to 104°F (0 to 40°C)
Relative humidity	5 to 95 percent noncondensing
<b>Nonoperating</b>	
Temperature	-13 to 158°F (-25 to 70°C)
Power consumption	25W maximum
<b>Physical Specifications</b>	
Dimensions (H x W x D)	1.70 x 6.80 x 12.25 in. (4.32 x 17.27 x 31.12 cm)
Weight (with power supply)	2.00 lb (0.91 kg)
<b>Regulatory and Standards Compliance</b>	
Safety	UL 60950, CSA C22.2 No. 60950, EN 60950 IEC 60950, AS/NZS60950
Electromagnetic compatibility (EMC)	CE marking, FCC Part 15 Class A, AS/NZS CISPR22 Class A, VCCI Class A, EN55022 Class A, CISPR22 Class A, EN61000-3-2, EN61000-3-3

### Cisco ASA 5580 Security Appliance Interface Cards

The Cisco ASA 5580 Adaptive Security Appliances are designed for ultimate interface flexibility and density with six interface card expansion slots supporting up to 24 Gigabit Ethernet ports; 12 10Gigabit Ethernet ports; or combinations thereof. These exceptional interface densities enable advanced security applications, including full-mesh high availability, multiple DMZs, virtual firewalls, and managed security. Gigabit Ethernet interfaces are available in 4-port copper or fiber configurations and 10Gigabit Ethernet is available in a 2-port fiber configuration. Gigabit Ethernet and 10Gigabit Ethernet fiber interfaces feature integrated short-range optics (SR) and an LC connector (Table 12).

**Table 12.** Characteristics of Cisco ASA 5580 Series Interface Cards

	Cisco ASA 5580 4-Port Gigabit Ethernet Copper	Cisco ASA 5580 4-Port Gigabit Ethernet Fiber	Cisco ASA 5580 2-Port 10Gigabit Ethernet Fiber
			
<b>Integrated 10/100/1000 Ports</b>	4	0	0
<b>Integrated 1000BASE-SX Ports</b>	0	4 with integrated short range optics, LC connector	0
<b>Integrated fiber 10 Gigabit Ethernet Ports</b>	0	0	2 with integrated short range optics, LC connector
<b>Wiring Support</b>	Category-5, unshielded twisted pair (UTP), 4-pair	Multimode fiber (62.5 µm or 50 µm)	Multimode fiber (62.5 µm or 50 µm)
<b>Power Consumption</b>	4.95 W (3.3V @ 1.5 A)	4.95 W (3.3V @ 1.5 A)	14 W (12V @ 1.17 A)
<b>Physical Specifications</b>			
<b>Weight</b>	Approx. 1lb	Approx. 1lb	Approx. 1lb

### Ordering Information

To place an order, visit the [Cisco Ordering Home Page](#). Table 13 provides ordering information for the Cisco ASA 5500 Series.

**Table 13.** Ordering Information

Product Name	Part Number
<b>Cisco ASA 5500 Series Firewall Edition Bundles</b>	
Cisco ASA 5505 10-User Bundle includes 8-port Fast Ethernet switch, 10 IPsec VPN peers, 2 SSL VPN peers, Triple Data Encryption Standard/Advanced Encryption Standard (3DES/AES) license	ASA5505-BUN-K9
Cisco ASA 5505 10-User Bundle includes 8-port Fast Ethernet switch, 10 IPsec VPN peers, 2 SSL VPN peers, Data Encryption Standard (DES) license	ASA5505-K8
Cisco ASA 5505 50-User Bundle includes 8-port Fast Ethernet switch, 10 IPsec VPN peers, 2 SSL VPN peers, 3DES/AES license	ASA5505-50-BUN-K9
Cisco ASA 5505 Unlimited-User Bundle includes 8-port Fast Ethernet switch, 10 IPsec VPN peers, 2 SSL VPN peers, 3DES/AES license	ASA5505-UL-BUN-K9
Cisco ASA 5505 Unlimited-User Security Plus Bundle includes 8-port Fast Ethernet switch, 25 IPsec VPN peers, 2 SSL VPN peers, DMZ, stateless Active/Standby high availability, 3DES/AES license	ASA5505-SEC-BUN-K9
Cisco ASA 5510 Firewall Edition includes 3 Fast Ethernet interfaces, 250 IPsec VPN peers, 2 SSL VPN peers, 3DES/AES license	ASA5510-BUN-K9
Cisco ASA 5510 Firewall Edition includes 3 Fast Ethernet interfaces, 250 IPsec VPN peers, 2 SSL VPN peers, DES license	ASA5510-K8
Cisco ASA 5510 Security Plus Firewall Edition includes 2 Gigabit Ethernet + 3 Fast Ethernet interfaces, 250 IPsec VPN peers, 2 SSL VPN peers, Active/Standby high availability, 3DES/AES license	ASA5510-SEC-BUN-K9
Cisco ASA 5520 Firewall Edition includes 4 Gigabit Ethernet interfaces + 1 Fast Ethernet interface, 750 IPsec VPN peers, 2 SSL VPN peers, Active/Active and Active/Standby high availability, 3DES/AES license	ASA5520-BUN-K9
Cisco ASA 5520 Firewall Edition includes 4 Gigabit Ethernet interfaces + 1 Fast Ethernet interface, 750 IPsec VPN peers, 2 SSL VPN peers, Active/Active and Active/Standby high availability, DES license	ASA5520-K8
Cisco ASA 5540 Firewall Edition includes 4 Gigabit Ethernet interfaces + 1 Fast Ethernet interface, 5000 IPsec VPN peers, 2 SSL VPN peers, 3DES/AES license	ASA5540-BUN-K9
Cisco ASA 5540 Firewall Edition includes 4 Gigabit Ethernet interfaces + 1 Fast Ethernet interface, 5000 IPsec VPN peers, 2 SSL VPN peers, DES license	ASA5540-K8
Cisco ASA 5550 Firewall Edition includes 8 Gigabit Ethernet interfaces + 1 Fast Ethernet interface, 4 Gigabit SFP interfaces, 5000 IPsec VPN peers, 2 SSL VPN peers, 3DES/AES license	ASA5550-BUN-K9
Cisco ASA 5550 Firewall Edition includes 8 Gigabit Ethernet interfaces + 1 Fast Ethernet interface, 4 Gigabit SFP interfaces, 5000 IPsec VPN peers, 2 SSL VPN peers, DES license	ASA5550-K8
Cisco ASA 5580-20 Firewall Edition includes 2 management interfaces, 5000 IPsec VPN peers, 2 SSL VPN peers, DES license	ASA5580-20-BUN-K8
Cisco ASA 5580-20 Firewall Edition includes 2 management interfaces, 5000 IPsec VPN peers, 2 SSL VPN peers, 3DES/AES license	ASA5580-20-BUN-K9
Cisco ASA 5580-20 Firewall Edition 4 Gigabit Ethernet Bundle includes 4 Gigabit Ethernet interfaces, 2 management interfaces, 5000 IPsec VPN peers, 2 SSL VPN peers, Dual AC power, 3DES/AES license	ASA5580-20-4GE-K9
Cisco ASA 5580-20 Firewall Edition 8 Gigabit Ethernet Bundle includes 8 Gigabit Ethernet interfaces, 2 management interfaces, 5000 IPsec VPN peers, 2 SSL VPN peers, Dual AC power, 3DES/AES license	ASA5580-20-8GE-K9
Cisco ASA 5580-40 Firewall Edition includes 2 management interfaces, 5000 IPsec VPN peers, 2 SSL VPN peers, DES license	ASA5580-40-BUN-K8
Cisco ASA 5580-40 Firewall Edition includes 2 management interfaces, 5000 IPsec VPN peers, 2 SSL VPN peers, 3DES/AES license	ASA5580-40-BUN-K9
Cisco ASA 5580-40 Firewall Edition 8 Gigabit Ethernet Bundle includes 8 Gigabit Ethernet interfaces, 2 management interfaces, 5000 IPsec VPN peers, 2 SSL VPN peers, Dual AC power, 3DES/AES license	ASA5580-40-8GE-K9
Cisco ASA 5580-40 Firewall Edition 4 10Gigabit Ethernet Bundle includes 4 10Gigabit Ethernet interfaces; 2 management interfaces; 5000 IPsec VPN peers; 2 SSL VPN peers, Dual AC power, 3DES/AES license	ASA5580-40-10GE-K9
<b>Cisco ASA 5500 Series IPS Edition Bundles</b>	
Cisco ASA 5510 IPS Edition includes AIP-SSM-10, firewall services, 250 IPsec VPN peers, 2 SSL VPN peers, 3 Fast Ethernet interfaces	ASA5510-AIP10-K9



Product Name	Part Number
Cisco ASA 5520 IPS Edition includes AIP-SSM-10, firewall services, 750 IPsec VPN peers, 2 SSL VPN peers, 4 Gigabit Ethernet interfaces, 1 Fast Ethernet interface	ASA5520-AIP10-K9
Cisco ASA 5520 IPS Edition includes AIP-SSM-20, firewall services, 750 IPsec VPN peers, 2 SSL VPN peers, 4 Gigabit Ethernet interfaces, 1 Fast Ethernet interface	ASA5520-AIP20-K9
Cisco ASA 5540 IPS Edition includes AIP-SSM-20, firewall services, 5000 IPsec VPN peers, 2 SSL VPN peers, 4 Gigabit Ethernet interfaces, 1 Fast Ethernet interface	ASA5540-AIP20-K9
<b>Cisco ASA 5500 Series Content Security Edition Bundles</b>	
Cisco ASA 5510 Content Security Edition includes CSC-SSM-10, 50-user antivirus/anti-spyware with 1-year subscription, firewall services, 250 IPsec VPN peers, 2 SSL VPN peers, 3 Fast Ethernet interfaces	ASA5510-CSC10-K9
Cisco ASA 5510 Content Security Edition includes CSC-SSM-20, 500-user antivirus/anti-spyware with 1-year subscription, firewall services, 250 IPsec VPN peers, 2 SSL VPN peers, 3 Fast Ethernet interfaces	ASA5510-CSC20-K9
Cisco ASA 5520 Content Security Edition includes CSC-SSM-10, 50-user antivirus/anti-spyware with 1-year subscription, firewall services, 750 IPsec VPN peers, 2 SSL VPN peers, 4 Gigabit Ethernet interfaces, 1 Fast Ethernet interface	ASA5520-CSC10-K9
Cisco ASA 5520 Content Security Edition includes CSC-SSM-20, 500-user antivirus/anti-spyware with 1-year subscription, firewall services, 750 IPsec VPN peers, 2 SSL VPN peers, 4 Gigabit Ethernet interfaces, 1 Fast Ethernet interface	ASA5520-CSC20-K9
<b>Cisco ASA 5500 Series SSL/IPsec VPN Edition Bundles</b>	
Cisco ASA 5505 SSL/IPsec VPN Edition includes 10 IPsec VPN peers, 10 SSL VPN peers, 50 firewall users, 8-port Fast Ethernet switch	ASA5505-SSL10-K9
Cisco ASA 5505 SSL/IPsec VPN Edition includes 25 IPsec VPN peers, 25 SSL VPN peers, 50 firewall users, 8-port Fast Ethernet switch	ASA5505-SSL25-K9
Cisco ASA 5510 SSL/IPsec VPN Edition includes 250 IPsec VPN peers, 50 SSL VPN peers, firewall services, 3 Fast Ethernet interfaces	ASA5510-SSL50-K9
Cisco ASA 5510 SSL/IPsec VPN Edition includes 250 IPsec VPN peers, 100 SSL VPN peers, firewall services, 3 Fast Ethernet interfaces	ASA5510-SSL100-K9
Cisco ASA 5510 SSL/IPsec VPN Edition includes 250 IPsec VPN peers, 250 SSL VPN peers, firewall services, 3 Fast Ethernet interfaces	ASA5510-SSL250-K9
Cisco ASA 5520 SSL/IPsec VPN Edition includes 750 IPsec VPN peers, 500 SSL VPN peers, firewall services, 4 Gigabit Ethernet interfaces, 1 Fast Ethernet interface	ASA5520-SSL500-K9
Cisco ASA 5540 SSL/IPsec VPN Edition includes 5000 IPsec VPN peers, 1000 SSL VPN peers, firewall services, 4 Gigabit Ethernet interfaces, 1 Fast Ethernet interface	ASA5540-SSL1000-K9
Cisco ASA 5540 SSL/IPsec VPN Edition includes 5000 IPsec VPN peers, 2500 SSL VPN peers, firewall services, 4 Gigabit Ethernet interfaces, 1 Fast Ethernet interface	ASA5540-SSL2500-K9
Cisco ASA 5550 SSL/IPsec VPN Edition includes 5000 IPsec VPN peers, 2500 SSL VPN peers, firewall services, 8 Gigabit Ethernet interfaces, 1 Fast Ethernet interface	ASA5550-SSL2500-K9
Cisco ASA 5550 SSL/IPsec VPN Edition includes 5000 IPsec VPN peers, 5000 SSL VPN peers, firewall services, 8 Gigabit Ethernet interfaces, 1 Fast Ethernet interface	ASA5550-SSL5000-K9
Cisco ASA 5580 SSL/IPsec VPN Edition includes 10,000 IPsec VPN peers, 10,000 SSL VPN peers, firewall services, 4 Gigabit Ethernet interfaces, 2 management interfaces, Dual AC power, 3DES/AES license	ASA5580-20-10K-K9
<b>Security Services Modules</b>	
Cisco ASA Advanced Inspection and Prevention Security Services Module 10	ASA-SSM-AIP-10-K9=
Cisco ASA Advanced Inspection and Prevention Security Services Module 20	ASA-SSM-AIP-20-K9=
Cisco ASA Content Security and Control Security Services Module 10 with 50-user antivirus/anti-spyware, 1-year subscription	ASA-SSM-CSC-10-K9=
Cisco ASA Content Security and Control Security Services Module 20 with 500-user antivirus/anti-spyware, 1-year subscription	ASA-SSM-CSC-20-K9=
Cisco ASA 4-Port Gigabit Ethernet Security Services Module	SSM-4GE=
<b>Cisco ASA 5580 Series Interface Expansion Cards</b>	
Cisco ASA 5580 4-port 10/100/1000 Ethernet interface card, RJ45	ASA5580-4GE-CU=
Cisco ASA 5580 4-port Gigabit Ethernet fiber interface card, SR, LC	ASA5580-4GE-FI=
Cisco ASA 5580 2-port 10 Gigabit Ethernet fiber interface card, SR, LC	ASA5580-2X10GE-SR=

Product Name	Part Number
<b>Cisco ASA 5500 Series Software</b>	
Cisco ASA Software one-time upgrade for nonsupport customers	ASA-SW-UPGRADE=
<b>Cisco ASA 5500 Series Accessories</b>	
Cisco ASA 5500 Series compact flash, 256 MB	ASA5500-CF-256MB=
Cisco ASA 5500 Series compact flash, 512 MB	ASA5500-CF-512MB=
Cisco ASA 180W AC power supply	ASA-180W-PWR-AC=
Gigabit Ethernet optical SFP connector, 1000BASE-SX short-wavelength transceiver	GLC-SX-MM=
Gigabit Ethernet optical SFP connector, 1000BASE-LX/LH long-wavelength/long-haul transceiver	GLC-LH-SM=
Cisco ASA 5580 Spare AC Power Supply	ASA5580-PWR-AC=
Cisco ASA 5580 Spare Rail Kit	ASA5580-RAILS=

### To Download the Software

Visit the [Cisco Software Center](#) to download Cisco ASA Software.

### Service and Support

Cisco services help you protect your network investment, optimize network operations, and prepare your network for new applications to extend network intelligence and the power of your business.

Included in the Operate phase of the lifecycle are Cisco Security Intellishield Alert Manager Service, SMARTnet, Service Provider Base, and Cisco Services for IPS. These services are suitable for Enterprise, Commercial and Services Provider customers.

Cisco Security Intellishield Alert Manager Service provides a customizable, web-based threat and vulnerability alert service that allows organizations to easily access timely, accurate and credible information about potential vulnerabilities in their environment.

“Cisco Services for IPS” supports modules, platforms, and bundles of platforms and modules that feature IPS functionality. SMARTnet and Service Provider Base support other products in this family.

### For More Information

For more information, please visit the following links:

- Cisco ASA 5500 Series Adaptive Security Appliance: <http://www.cisco.com/go/asa>
- Cisco Adaptive Security Device Manager: <http://www.cisco.com/go/asdm>
- Cisco Security Services:  
[http://www.cisco.com/en/US/products/svcs/ps2961/ps2952/serv\\_group\\_home.html](http://www.cisco.com/en/US/products/svcs/ps2961/ps2952/serv_group_home.html)



Americas Headquarters  
Cisco Systems, Inc.  
San Jose, CA

Asia Pacific Headquarters  
Cisco Systems (USA) Pte. Ltd.  
Singapore

Europe Headquarters  
Cisco Systems International BV  
Amsterdam, The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices)

CCDE, CCVP, Cisco EEM, Cisco StadiumVision, the Cisco logo, COE, and Welcome to the Human Network are trademarks. Changing the Way We Work, Live, Play and Learn is a service mark, and Access Registrar, Aronix, AsyncOS, Bringing the Meeting To You, Catalyst, CCDA, CCDP, CCIE, CCR, CCNA, CCNP, CCSP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Collaboration Without Limitation, Enterprise/Solver Ether/Chemel, EtherFast, EtherSwitch, Event Center, Fast Step, Follow Me Presence, FormShare, GeoDrive, HomeLink, Internet Companion, IOS, IPPhone, IPTV, IQ Expertise, the IQ logo, IQ Net, iQ Ready, iQ Ready: Seeboard, iQuick Study, IronPort, the IronPort logo, LightStream, Linksys, MediaTone, MeetingPlace, MGX, Netwitness, Networking Academy, Network Registrar, PCNow, PIX, PowerPanel, ProCommand, ScriptShare, SenderBase, SMARTnet, Spectrum Expert, StackWise, The Future. Way to Increase Your Return: Quotion, TransPath, WebEx, and the WebEx logo are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of this word, partner does not imply a partnership relationship between Cisco and any other company. (S) 2008 [R]