

iS-220DPB



1680x1050 RESOLUTION	5ms RESPONSE TIME	X-CONTRAST 3000:1 CONTRAST RATIO	16:10 ASPECT RATIO	HIGH BRIGHTNESS	ULTRA-WIDE VIEWING ANGLE	BUILT-IN STEREO SPEAKERS	USER-FRIENDLY MENU SCREEN	TILT	VESA WALL-MOUNTABLE	VGA + DVI INPUTS
----------------------	-------------------	----------------------------------	--------------------	-----------------	--------------------------	--------------------------	---------------------------	------	---------------------	------------------

Technical Specifications

1. Display Size/Type	22" Widescreen Active Matrix TFT LCD	20. Input Voltage	100VAC-240VAC, 50/60Hz Autodetect
2. Resolution	1680 x 1050 (WXGA+)	21. Power Consumption	55W Maximum
3. Aspect Ratio	16:10	22. Operating Temperature	5°C~40°C / 41°F~104°F
4. Pixel Pitch	0.282(H)mm x 0.282(V)mm	23. Humidity	20%~80%
5. Brightness	300cd/m ²	24. Net Dimensions	20.1"(W) x 16.7"(H) x 8.8"(D)
6. Response Time	5ms (Typical)	25. Net Weight	10.8 bs.
7. Contrast Ratio	3000:1 X-Contrast, 1000:1 (Typical)	26. Gross Dimensions	22.4"(W) x 14.8"(H) x 5.4"(D)
8. Displayable Colors	16.7 Million	27. Gross Weight	14.8 lbs.
9. Viewing Angle (H/V)	170°/160°	28. Certifications	FCC, UL/CUL, EnergyStar
10. Color Temperature	Warm, Nature, Cool, User Mode	29. Package Contents	iS-220DPB, VGA Cable, Audio Cable, Power Cable, User Manual CD-ROM, Quick Start Guide, Warranty Card
11. Panel Treatment	Anti-Glare Hardcoating	30. UPC Code	842651003272
12. Horizontal Frequency	24kHz - 94kHz	31. Warranty	1-Year Limited
13. Vertical Frequency	56kHz - 76kHz		
14. Video Input(s)	15-Pin D-SUB (VGA), DVI		
15. Speakers	1.5W x 2 Channel Built-in Stereo		
16. Headphone Out	NA		
17. Tilt	0°~20°		
18. Kensington Slot	Yes		
19. VESA Mounting	100mm x 100mm		

